

Hydraulic Regulators


Self-Relieving Regulators

1/4" FEMALE NPT, 30 - 150 PSI MAX OUTPUT, 10,000 PSI MAX INLET

Model 28SM2 STD., 28SM3 H2S, 28SM4 ARCTIC




Conforms to the SEP category of the European Pressure Equipment Directive
Issue No. 97/23/EC



The **28SM2** is a self-relieving, two position, pressure reducing (spring/sensing piston modulating combination), flow control valve. Pressure Regulators are typically used to reduce source or instrument supply pressure from up to 10,000 PSI to a specific lower operating pressure, generally from 30-150 PSI. The reduced operating pressure provided from the Regulator outlet connection will be maintained within a predetermined operating pressure range or limit, required by the receiving control circuit or a control device.

Turning the Adjustment Knob clockwise will increase the spring exerted tension to increase the Regulator output pressure. Rotating the Adjustment Knob counterclockwise will decrease the Regulator output pressure. Once the exact operating output pressure is achieved, the Lock Nut (2) should be tightened against the Spring Housing to maintain the appropriate output pressure setting.



PARTS LIST:

- | | |
|--------------------|------------------------|
| 1. Adjustment Knob | 11. SS Porous Filter * |
| 2. Hex Lock Nut | 12. Retainer |
| 3. Panel Nut | 13. Spring |
| 4. Spring Guide | 14. Seat Guide * |
| 5. Sensing Piston | 15. Seat Back Up |
| 6. Torlon Seat * | 16. Viton O Ring * |
| 7. Viton O Ring * | 17. Back Up Ring * |
| 8. Valve Body | 18. Spring |
| 9. Viton O Ring * | 19. Spring Housing |
| 10. Valve Pin * | 20. Panel Seal Ring |

* Indicates parts included in a Repair Kit

Sigma Model Number 28SM2

1/4" FEMALE NPT, 30 - 150 PSI MAX OUTPUT, 10,000 PSI MAX INLET

Product Specifications

Control Function: Pressure Reducing Flow Control (High Pressure In - Low Pressure Out),
Self-relieving downstream overpressure type

Body Pressure Rating: 10,000 PSI maximum (690 bar) Inlet pressure

Adjustment Range Capability (Regulated Pressure): 30 - 150 PSI maximum outlet pressure

Manual Pressure Adjusting Operator: Knob (360° Rotating Screw)

Media Service: Hydraulic

Connection Size (Body): 1/4-18 Female N.P.T. Inlet and Outlet, 1/8-27 N.P.T. Relief Port

Cv Factor: .11

Component Material (Metal): 316 Stainless Steel and 17-4PH SS

Seal Material: Viton Orings, Torlon, **Arctic:** Buna and HBNR

Panel Mount: Yes

Panel Hole Cutout Size Required: 1 diameter

Weight: 5 Lbs.

Operating Temperature: -20° F to +250° F (-29° C to +121° C)

Overall Dimensions: 6-3/4 Height x 2-1/2 Diameter (17.15 cm Height x 6.35 cm Diameter)

Pressure Equipment Directive (PED): This product conforms to the SEP Category of the European P.E.D.

Shelf Position Port Status

<u>Inlet Supply</u>	High Pressure Fluid Inlet Open to Outlet
<u>Outlet</u>	Reduced Pressure Output (to receiving control circuit)

Repair Kit Information

Repair Kits contain all of the Seals and other components typically replaced when repairing the assembly. In order to maintain optimum operating control function.